

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.1

Issue date: 08/19/2022 Revision date: 09/23/2022 Supersedes: 08/19/2022

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : NATURAL PEAR FLAVOR - MCT

Product code : TBMCT112

1.2. Recommended use and restrictions on use

1.3. Supplier

EXTRACT CONSULTANTS, LLC. TERPENES - FLAVORS - BASES PO BOX 11433, DENVER, CO 80211 www.extractconsultants.com INFORMATION: 1-888-541-9089

1.4. Emergency telephone number

Emergency number : CHEMTREC - USA: 800-424-9300 International: +1 703-527-3887 / 1-800-424-9300

CCN 13010

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 Combustible liquid

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Signal word (GHS US) : Warning

Hazard statements (GHS US) : Combustible liquid

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
ISOBUTYL ACETATE	(CAS-No.) 110-19-0	1 – 5	Flam. Liq. 2, H225 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

09/23/2022 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

NATURAL PEAR FLAVOR - MCT

No additional information available

ISOBUTYL ACETATE (110-19-0)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

09/23/2022 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : COLORLESS TO YELLOW

Odor : CHARACTERISTIC, MATCHING RETAINER SAMPLE

Odor threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available

Flash point : 70 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 0.9353 (0.9253 – 0.9453)

Solubility : Insoluble.

Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity, kinematic No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available : No data available Oxidizing properties

9.2. Other information

Refractive index : 1.44736 (1.43736 – 1.45736)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

09/23/2022 EN (English US) 3/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) Not classified Skin corrosion/irritation Serious eve damage/irritation : Not classified Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified : Not classified Reproductive toxicity

STOT-single exposure : Not classified

ISOBUTYL ACETATE (110-19-0)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

09/23/2022 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : NA1993 Combustible liquid, n.o.s. (CIS-3-HEXENYL BUTYRATE, ETHYL-2-METHYL

BUTYRATE) - Regulated for Bulk Only, Comb Liq, III

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

(CIS-3-HEXENYL BUTYRATE, ETHYL-2-METHYL BUTYRATE) - Regulated for Bulk Only

Class (DOT) : Comb Liq - Combustible liquid

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN

requiring a technical name

DOT Special Provisions (49 CFR 172.102) : 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for

transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for

blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)).

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal...... 178.275(d)(2)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

1

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

ISOBUTYL ACETATE (110-19-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

09/23/2022 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

ISOBUTYL ACETATE (110-19-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

WARNING:

This product can expose you to myrcene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

go to www. corrannings.sa.gov.		
Component	State or local regulations	
ISOBUTYL ACETATE (110-19-0)	U.S New Jersey - Right to Know Hazardous Substance List	

SECTION 16: Other information

Revision date : 09/23/2022

Full text of H-phrases:

•••	in took of 11 princess.		
	H225	Highly flammable liquid and vapor	
	H336	May cause drowsiness or dizziness	

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

09/23/2022 EN (English US) 6/6